International Application No.: PCT/JP03/14712 International Filing Date: November 19, 2003

Preliminary Amendment Accompanying

Substitute Specification

## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

1. (Currently Amended) A method for recording data in an optical recording medium wherein the optical recording medium includes a substrate, a protective layer and a plurality of information recording layers between the substrate and the protective layer—and—a laser—beam—is projected onto the plurality of information recording layers via a light—incidence—plane—constituted—by—either the substrate or the protective layer, thereby recording data in the plurality of information recording layers, the method for recording data in an optical recording medium comprising; steps of

projecting a laser beam onto the plurality of information recording layers whose power is modulated between at least three levels including a level corresponding to a recording power, a level corresponding to an intermediate power lower than the recording power and a level corresponding to a bottom power lower than the intermediate power onto at least one information recording layer other than an information recording layer farthest from the light incidence plane and

¥.,

forming a recording mark in the at least one information recording layer other than the information recording layer farthest from the light incidence plane, thereby recording data therein.

2. (Original) A method for recording data in an optical recording medium in accordance with Claim 1, wherein the level of the bottom power is set so that a region of the at least one information recording layer other than the information recording layer farthest from the light incidence plane heated by irradiation with the laser

International Application No.: PCT/JP03/14712 International Filing Date: November 19, 2003

Preliminary Amendment Accompanying

Substitute Specification

beam whose power is set to the recording power can be cooled during irradiation with the laser beam whose power is set at the bottom power.

3. (Original) A method for recording data in an optical recording medium in accordance with Claim 1, wherein the power of the laser beam is set to the bottom power when it is projected onto the end portion of each of the recording marks.

4. (Original) A method for recording data in an optical recording medium in accordance with Claim 2, wherein the power of the laser beam is set to the bottom power when it is projected onto the end portion of each of the recording marks.

5. (Original) A method for recording data in an optical recording medium in accordance with Claim 1, wherein the power of the laser beam is set to the intermediate power when it is projected onto a region between neighboring recording marks to be formed in the at least one information recording layer other than the information recording layer farthest from the light incidence plane.

- 6. (Original) A method for recording data in an optical recording medium in accordance with Claim 2, wherein the power of the laser beam is set to the intermediate power when it is projected onto a region between neighboring recording marks to be formed in the at least one information recording layer other than the information recording layer farthest from the light incidence plane.
- 7. (Original) A method for recording data in an optical recording medium in accordance with Claim 3, wherein the power of the laser beam is set to the intermediate power when it is projected onto a region between neighboring recording

International Application No.: PCT/JP03/14712 International Filing Date: November 19, 2003

Preliminary Amendment Accompanying

Substitute Specification

marks to be formed in the at least one information recording layer other than the information recording layer farthest from the light incidence plane.

8. (Original) A method for recording data in an optical recording medium in accordance with Claim 4, wherein the power of the laser beam is set to the intermediate power when it is projected onto a region between neighboring recording marks to be formed in the at least one information recording layer other than the information recording layer farthest from the light incidence plane.

9. (Original) A method for recording data in an optical recording medium in accordance with Claim 3, wherein the power of the laser beam is modulated so that a time period during which the power of the laser beam is set to the bottom power for forming the end portion of each of the recording marks becomes longer as a linear recording velocity is higher.

- 10. (Original) A method for recording data in an optical recording medium in accordance with Claim 4, wherein the power of the laser beam is modulated so that a time period during which the power of the laser beam is set to the bottom power for forming the end portion of each of the recording marks becomes longer as a linear recording velocity is higher.
- 11. (Original) A method for recording data in an optical recording medium in accordance with Claim 7, wherein the power of the laser beam is modulated so that a time period during which the power of the laser beam is set to the bottom power for forming the end portion of each of the recording marks becomes longer as a linear recording velocity is higher.

International Application No.: PCT/JP03/14712 International Filing Date: November 19, 2003

Preliminary Amendment Accompanying

Substitute Specification

12. (Original) A method for recording data in an optical recording medium in accordance with Claim 8, wherein the power of the laser beam is modulated so that a time period during which the power of the laser beam is set to the bottom power for forming the end portion of each of the recording marks becomes longer as a linear

recording velocity is higher.

13. (Original) A method for recording data in an optical recording

medium in accordance with Claim 1, wherein data are recorded by employing an

objective lens and a laser beam whose numerical aperture NA and wavelength  $\boldsymbol{\lambda}$  satisfy

 $NNA \le 640$  nm, and projecting the laser beam onto the optical recording medium via the

objective lens.

14. (Original) A method for recording data in an optical recording

medium in accordance with Claim 2, wherein data are recorded by employing an

objective lens and a laser beam whose numerical aperture NA and wavelength  $\lambda$  satisfy

 $NA \le 640$  nm, and projecting the laser beam onto the optical recording medium via the

objective lens.

15. (Original) A method for recording data in an optical recording

medium in accordance with Claim 1, wherein the protective layer is formed of a light

transmissible material and the laser beam is projected onto the plurality of the

information recording layers via the protective layer.

16. (Original) A method for recording data in an optical recording

medium in accordance with Claim 2, wherein the protective layer is formed of a light

transmissible material and the laser beam is projected onto the plurality of the

information recording layers via the protective layer.

6

International Application No.: PCT/JP03/14712 International Filing Date: November 19, 2003 Preliminary Amendment Accompanying

**Substitute Specification** 

17. (New) An apparatus for recording data in an optical recording medium wherein the optical recording medium includes a substrate, a protective layer and a plurality of information recording layers between the substrate and the protective layer and a laser beam is projected onto the plurality of information recording layers via a light incidence plane constituted by either the substrate or the protective layer, thereby recording data in the plurality of information recording layers, the apparatus for recording data in an optical recording medium being constituted so as to project a laser beam whose power is modulated between at least three levels including a level corresponding to a recording power, a level corresponding to an intermediate power lower than the recording power and a level corresponding to a bottom power lower than the intermediate power onto at least one information recording layer other than an information recording layer farthest from the light incidence plane and form a recording layer farthest from the light incidence plane, thereby recording data therein.

18. (New) An optical recording medium which includes a substrate, a protective layer and a plurality of information recording layers between the substrate and the protective layer and is constituted so that a laser beam is projected onto the plurality of information recording layers via a light incidence plane constituted by either the substrate or the protective layer, thereby recording data in the plurality of information recording layers, the optical recording medium being recorded with data for setting data recording conditions necessary for projecting a laser beam whose power is modulated between at least three levels including a level corresponding to a recording power, a level corresponding to an intermediate power lower than the recording power and a level corresponding to a bottom power lower than the intermediate power onto at least one information recording layer other than an information recording layer farthest from the light incidence plane when a recording mark is to be formed in the at least one

International Application No.: PCT/JP03/14712 International Filing Date: November 19, 2003 Preliminary Amendment Accompanying

**Substitute Specification** 

information recording layer other than an information recording layer farthest from the light incidence plane, thereby recording data therein.